

## Department 22 Contest

### Montour DeLong Community Fair Tractor & 4 Wheel Vehicle Pulls General Rules.

Sponsored by Montour Antique Farm Machinery Association.

**Chairman – Co-Chairs:** Chris Fry and Paul Wertz

**Committee:** Ken Cotner Jr., John Esenwein, Don Hilkert, Owen Hilkert, Gus Jones, Mike Shultz, Ryan Styer, Craig Ulmer, and Michael Woodruff

#### GENERAL RULES

##### **\*ATTENTION\***

MONTOUR DELONG COMMUNITY FAIR ASSOCIATION AND MONTOUR ANTIQUE FARM MACHINERY COLLECTORS' ASSOCIATION WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO TRACTORS/TRUCKS OR INJURY TO CONTESTANTS OR ANYONE ELSE PARTICIPATING IN THIS CONTEST.

#### **GENERAL RULES FOR ALL CLASSES:**

1. All minors wishing to pull must pass a safety test performed by the committee **before fair** (ALL non-pace classes 16 years old).
  - a. 14 and 15-year-old drivers must have a safe-driving certificate for non-pace class and open classes.
2. Anyone under 18, tractor must have wheelie bars and a kill switch.
3. Those under 18 years of age must have written parental/guardian permission for each pull.
4. Any Tractor or driver found unsafe or illegal will be disqualified or barred from hooking.
5. Drivers must stay on the seat of the tractor. Hands must be on the steering wheel, hand brakes, hand clutch or throttle at all times during the pull. **Tractor must be in neutral when hooking/unhooking.**
6. Any part falling off the tractor after being hooked and until the tractor is unhooked will result in disqualification.
7. The Rules Committee will interpret all rules. The Rules Committee will rule on any unforeseen problems or oversights with their decisions being final.
8. A tractor can be entered only once in each class.
9. Registration is closed when that class starts.
10. All pulls will be started from a tight hitch.
11. Two starts will be given to change gears or weights within 75 feet. The sled may not be reset for pace classes at the discretion of the track officials.
12. Tractor must stay within boundaries of the course.
13. Pull is complete when forward motion of sled stops.
14. A limit of 2 minutes to start your pull when call may be implemented by track officials.
15. Tractor leaking uncontrolled excess fluid on the track prior to green flag will not be permitted to pull.
16. Any year tractor will be permitted to pull.
17. Pulling will be done from a stationary (in all directions) drawbar; fast hitches must be locked out.
18. All tractors running with a stroked crank must have side shields from radiator to bell housing.
19. The only fuels permitted are gasoline, diesel, and kerosene and LP gas.
20. ANY TRACTOR IN ANY CLASS RUNNING 20% OR MORE OVER STOCK RPM'S IS REQUIRED TO HAVE A SCATTER BLANKET AT THE BELL HOUSING AND SIDE SHIELDS FROM THE RADIATOR TO THE BELL HOUSING. For external flywheels turning over 20% stock RPM, the flywheel must be surrounded by a minimum of 3/8" steel that is 2" wider than the flywheel itself, and the fan blade must either be removed or be shrouded at least 12" behind radiator.

## 4 Wheel Drive Vehicle Pull

Monday August 8<sup>th</sup>, 2022, Registration and Weigh in 5:30 PM, Start 6:30 PM

<b>Dept. 22</b>	<b>4 Wheel Drive Vehicle Pull</b>
<b>Section 1</b>	<b>Entry Fee \$ 20.00</b>
<b>Premiums</b>	<b>1st-\$50.00 2nd-\$25.00 3rd-\$20.00 4th-\$15.00 5th-\$10.00</b>
<b>Class</b>	<b>Weight Classes:</b>
22301	Pro Street Gas 6,300
22302	Wild Street Gas 7,500
22303	Wild Street Diesel 8,500
22304	3.0 Diesel 8,000
22305	2.6 Diesel 8,000
22306	RWYA (Run What Ya Brung) 7,800

**THIS WILL BE THE TENTATIVE PULLING ORDER FOR THE NIGHT**

### **CLASS RULES:**

#### **GENERAL 4X4 RULES:**

1. Driver must be 18 years of age or older.
2. All contestants must sign waiver of liability.
3. First puller reserves the right to drop hook and come back at the end of the class.
4. If any concern of "cheating trucks" place in the top 5 of any class, they will be open to tech. Failure of allowing truck to be teched will result in disqualification
5. No one will be allowed on track area except contestants and track officials. Only one driver is allowed in vehicle.
6. The judges have the right to stop and disqualify the driver of any vehicle that is not being operated in a safe manner.
7. Violations of any rules shall constitute a disqualification.
8. All vehicles must be in neutral gear while being hitched and unhitched from the sled.
9. Vehicles must be stopped upon signal of judge.
10. Consumption of alcohol prior to or during event will result in disqualification
11. All pulls will start with a tight hitch. No jerking permitted. Contestants will have two attempts at moving the sled within 30 feet. Contestant will return to starting line on second attempt.
12. Committee reserves the right to change rules if necessary.

#### **All Classes Snyder County Rules (No points)**

1. <https://sctpapullers.com/rules>

## Farm Tractor Pulls – Light Hot Stock, Classic, Tractor Pull

Tuesday August 9<sup>th</sup>, 2022, Registration & Weigh in 5:30 PM, Start 6:30 PM

<b>Dept. 22</b>	<b>Light Hot Stock, Classic Tractor Pull</b>		
<b>Section 1</b>	Entry Fee \$20.00		
<b>Premiums</b>	<b>1<sup>st</sup> - \$50.00 2<sup>nd</sup> - \$25.00 3<sup>rd</sup> - \$20.00 4<sup>th</sup> - \$15.00 5<sup>th</sup> - \$10.00</b>		
<b>Class</b>	<b>Weight</b>	<b>Description</b>	<b>Tire Sizes</b>
22100	5,500	Light Hot Stock	18.4x38
22101	5,500	Classic	18.4x38
22102	6,000	Light Hot Stock	18.4
22103	6,500	Classic	18.4
22104	7,000	Light Hot Stock	18.4
22105	10,000	Hot Stock (SCTPA Points)	Snyder County Rules & Payout
22106	12,000	Enhanced Farm (SCTPA Points)	Snyder County Rules & Payout

### Light Hot Stock and Classic Rules:

1. General Rules Apply
2. Any cut is allowed on the tires - front, V-cuts, double cuts, etc.
3. Drawbar must be minimum length of 18" from center of axle to point of hook, parallel to ground and 20" from top of hitching devices to ground. Fast hitches must be locked out.
4. No weights may extend more than 6" beyond rear tires except orchard or utility style tractors; front weights may not extend more than 11 feet forward from center of rear axle.
5. No chains or dual wheels permitted. Four-wheel drive tractors must have front wheels disengaged.
6. Drawbar must be equipped with a clevis or hitching device not more than 1" thick ( $\frac{3}{4}$ " to 1") and must have a 3" diameter opening. Pulling point may not be more than 1 ½" back of hitching device. Hitch must be unobstructed by weights.
7. Classic tractors must have fenders with no sharp edges or corners.
8. Tractors must have a kill switch.
9. Engine must be agriculture or industrial type engine for all Light Hot Stock tractors. Automotive type engine for Classic tractors.
10. Tractors must have wheelie bars that extend 5" beyond radius of rear tires and no more than 10" above the ground.
11. Exhaust pipe must extend above steering wheel and be straight – no curves in the pipe that would project internal parts into the stands.
12. Tractors must have fire extinguisher reachable from seat.
13. All tractors must have side shields from radiator to bell housing.
14. ALL "CLASSIC" TRACTORS MUST BE EQUIPPED WITH A DEAD MANS THROTTLE WITH DOUBLE SPRINGS.
15. CLASSES MAY BE ADDED, DROPPED OR CHANGED TO SUIT ATTENDANCE.

### Lawn Stock Garden Tractor Pulls

**Wednesday, August 10<sup>th</sup>, 2022, Registration & weigh in 5:30 PM, Start 6:30 PM**

**Committee:** Paul Faus 570-394-8857, Dennis Faus 570-441-8688

<b>Dept. 22</b>	<b>Lawn Stock Garden Tractor Pulls</b>
<b>Section 1</b>	Entry FEES \$10.00
<b>Premiums</b>	<b>1st-\$30.00 2nd-\$25.00 3rd-\$20.00 4th-\$15.00 5th-\$10.00</b>
<b>Class</b>	<b>Weight Classes:</b>
22240	800 lbs. Youth Stock — 14 hp and below
22241	900 lbs. Youth Stock — 14 hp and below
22242	1,050 Stock — 12 hp and under
22243	1,050 Stock — 14 hp and under
22244	1,050 Stock — 16 hp Single
22245	1,050 Stock Twin — 20 hp and under
22246	1,050 Stock Twin — 25 hp and under
22247	1,050 Max Stock — 14 hp and under
22248	1,050 Max Stock — 16 hp and under

1. ALL CLASSES: NO REAR WEIGHTS PAST REAR TIRE
2. Judges/Flagman's decision is final. Any disagreement of their decision on any point of controversy will result in disqualification in that class. Scale person has final say of weight and hitch height.
3. **BE RESPECTFUL TO WORKERS, PULLERS, AND FACILITY.**
4. Minimum of 1 1/2-inch hole hitch is required.
5. Each contestant will sign a waiver releasing the club, sponsors, and/or officers if any liability in case of an accident.
6. Tractors will always operate in a safe and orderly manner.
7. Club officers may disqualify any person under the influence of **drugs or alcohol** at any time and may be asked to leave the event.
8. Operators must be fully clothed including shoes. **No** open toed shoes or shorts.
9. Fire suits and fire-resistant boots or leather shoes are required in stock altered, super stock, and modified garden tractor classes.
  - a. Suits must be zipped and secured.
10. Helmets are required in stock altered, super stock, and modified classes including tractors jumping classes. All drivers under 16 are required to wear a helmet in all classes.
11. Operator must have tractor out of gear and hands off the steering wheel in view of person hooking tractor.
12. Driver must remain in seat with feet on footrest. They must always have at least one hand contacting the steering wheel during pull. Fingers cannot go between fender and tire; you may install handrail on fender to hang on to.
13. 20 horsepower and up: "L" brackets required on stock altered, super stock and modified garden tractors. They must be 6 inches high attaching at the rear most part of the wheelie bars and be attached by two points.
14. Draw bar must be horizontal and stationary in all directions. Must be at least 3/8-inch-thick minimum with a 1" A inch hole pulling point, with 3/8 inch minimum to 1 inch maximum from edge of hole to edge of hook plate towards the sled side. May not extend beyond rear tires and no higher than 13 inches off the ground. It shall not contact any part of the chain except the hook.
  - a. Clevis must be approved stock classes only.
  - b. Draw bar must be easily accessible.
15. Must have a 6 inch no zone around hitch point including top.
  - a. 3 inches on each side of hitch point.
16. All tractors must be equipped with foot pegs or running boards.

17. Fenders required may be fabricated. At least 4 inches by 12 inches (on top tire) coverage on fabricated fenders.
  - a. Must be able to support weight.
18. All safety equipment and weights must be secure. Wheel weight must be secure. Wheel weight rods must be covered. Tractor will be disqualified if any weights or equipment falls off and touches the ground while hooked to the sled.
  - a. Unforeseen driveline breakage does not disqualify the tractor or driver.
19. Engine exhaust must discharge vertically above the hood or below the frame. Stock tractors with mufflers in place are not required to comply.
20. Any portion of the tractor crossing over or touching the boundary line during a pull will result in disqualification. There is no "out of bounds" once the tractor passes the full pull mark, **EXCEPT** in pull of if the tractor goes "out of bounds" it will place last.
21. Batteries must be covered on all sides if not in stock location.
22. Tractor must be two-wheel drive, rubber tired.
  - a. No track type tractors.
  - b. No tire chains.
  - c. No steel or dual wheels.
23. All starts must be with a tight chain (no jerking starts).
24. Entrants will draw for position at the time of registration. Registration will be closed for each class at the start of that class.
25. In the event the contestant must make a repair at the time of their hook, they can drop 3 consecutive pulls or as time allows.
26. Pull-off contestants can add fuel and/or move weight before pull-off and make repairs if time allows.
27. No one except the driver and track officials will be allowed on the track during the pull; except children (under 13) needing adult supervision. No walking in front of the tractor; must be walking on the clutch side of the tractor.
28. Working zone for the track is 20 feet wide and 200 feet long minimum. Track to be determined day of the pull by sled operator.
29. All tractors may be protested. \$100 protest fee for single cylinder, \$200 protest fee for twin cylinders. Protest may be made by another participant in that class. If the tractor is found legal, that puller will get the \$100. If the tractor is found illegal, the protestor keeps the \$100. Tear down will be done at the end of pull day. The owner or designee of owner shall perform teardown. One tech official who is not competing in the same class and one board member shall perform the technical measurements and issue a pass or fail determination only.
  - a. If found illegal:
    - i. 1st offense — must be proven legal to compete again
    - ii. 2nd offense — tractor eliminated for remainder of year
30. No tractor may pull until tech/safety inspection has been performed and must have **CGTP** tech tag visible. Techs may **NOT** inspect their own tractors or and relation/family.
31. If you register and choose to leave before your class has pulled, you donate your money to the club.
  - a. Equipment breakage does not apply.
32. Driver's less than 18 years of age must have a signed parental consent form.
  - a. Minimum 5-13 years old for 14 horsepower youth stock.
  - b. Minimum of 13 years old for 20 horsepower, modified, stick altered, and super stock.
  - c. Parent/guardian is required for pullers up to age 13.
33. All tractors are required to have a kill switch with a 1-inch diameter ring at the rear of the tractor.
34. Stock tractors must have working reverse.

35. Max stock, stock altered, super stock, 3 cylinder, and diesel tractors must have a fire extinguisher securely fasted within easy reach of the driver.
36. All tractors must be equipped with wheelie bars. Point of contact should be NO more than 5 inches from the ground and NO less than 18 inches centers of the wheel. Tire skid plate needs to be at least 1 inch by 3 inches at ground contact and wheels need to be 1 inch by 4 inches diameter and must be strong enough to support weight of tractor (**NO** lightweight wheels).
37. Number 1 pull position will be the test puller. Contestant may take the pull **OR** come back 3<sup>rd</sup> **OR** come back last. Decision must be made **BEFORE** tractor is unhooked.
38. Driver and tractor may enter once per class. **ONLY** for youth drivers may a tractor be re-enter or entered more than once if **NOT** the same driver. (i.e., two children can use the same tractor).
39. Each contestant will be allowed two attempts of 25 feet to start the sled.
  - a. All classes may coast past the 50-foot mark.
  - b. Pull off contestants are allowed 1 attempt.
40. Each tractor and contestant must weigh in **BEFORE** each qualifying hook **INCLUDING** full pulls.

### Stock Class Rules

1. Tractor must have a 11-inch hitch height, with a minimum of a 1 1/2-inch hole.
2. Tractor must be stock in appearance of manufacturers hood, grill, fenders, and shell.
  - a. Fenders may be fabricated but must have at least 4 inches by 12-inch top of tread coverage and be able to support the weight.
3. Stock lift camshaft, stock stroke for engine model.
  - a. + .30 over bore allowed
  - b. Piston must remain flush or below top of block.
4. Engine does not need to be original but must remain in stock form.
  - a. **NO** adjustable flywheels allowed.
5. Wheelbase cannot be altered from original equipment.
6. Tractor frame can be modified for an engine change but may not be lengthened.
7. Must use stock unaltered carburetor— OEM carburetor for that model.
  - a. 10-12.5 Horsepower = 26 MM
  - b. 16-20 Horsepower = 30 MM
8. Must have air cleaner.
9. Maximum 3 cylinder, up to 20 Horsepower allowed.
  - a. **NO** adjustable flywheels allowed.
10. All fabricated seats must have a minimum of 3 inch back.
11. **NO** electric fuel pumps unless factory equipped.
12. Must use stock type ignition system. Chevy point allowed with cover.
13. Must use stock OEM head, surfacing allowed.
14. Maximum tire size is 23 X10:50 X 12 will be allowed if original equipment. (16hp and up can run 24x12x12 non cut tire)
  - a. **NO** professional pulling tires, paddle type or big bar tires.
  - b. Tread design may be bar or turf type.
  - c. Any style tire cutting permitted.
  - d. No ATV tires.
15. Tube front axles are allowed. (Must function as a stock axle).
  - a. Pivot in stock location.
  - b. Must be able to turn.
16. Front weight may not extend further than 7 feet from the center of the rear axle and weight may not extend more than 6 inches behind or above rear tires.

17. Transmission/transaxle must be original equipment for the tractor.
18. Must have working reverse.
19. **NO** pressurized fuel tanks.
20. **NO** intake standoffs or velocity stacks.
21. All flywheels, clutches, and pulley's must be equipped with shielding of other than original equipment. It must be 1/8 steel or equivalent.
22. RPMS must be controlled by the governor. **NO** external springs for any reason.
  - a. Maximum RPM limit — 4000 up to 12.5 Horsepower (NO LOAD).
  - b. Maximum RPM limit — 4000 RPM 16 Horsepower & 20 Horsepower (can run 24x12x12 tires)
23. Modification to clutch, driveline, and transaxle are allowed

### **Stock Altered or Pro-Stock**

1. **Chassis:** Tractors shall be stock in appearance and utilize stock sheet metal Factory stock, commercially available, cast block engine. Typical manufacturers of the engines would be. Kohler, Tecumseh, Wisconsin, Onan, Briggs and station. Slight frame rail modifications may be made to accept engine. Chassis must be original Wheelbase may be lengthened to 52 inches by moving FRONT AXLE ONLY. Wheelie bars are required (same as general rules). Hitch point maximum height 13 inches (same as general rules). Fire extinguisher is required.
2. **Engine:** Engines must be commercially manufactured brands such as Kohler, Tecumseh, Wisconsin, Onan, Briggs. NO after-market blocks are allowed. Engines must be of single- or two-cylinder design, air or liquid cooled, four cycle, flat head or overhead valve. Maximum overbore is ft3 inches. Porting and polishing are allowed. Non-stock camshaft is permitted. Engine must retain stock size values and stock crankshaft lift and stroke. Up to a 1-inch carburetor must be used or the original equipment model. Engine must retain stock appearance. NO billet heads are allowed. Engine must have a functioning governor and stock ignition. May utilize billet steel or billet aluminum flywheels. Pump gas only. NO additives (except lead additive). NO alcohol, nitrous, oxide, or nitro-methane allowed. NO pressurized fuel tanks. 20 horsepower maximum and 4500 RPM maximum. Allowed to use adjustable push rods, adjustable flywheel, velocity stack, carburetor adapter up to 1 inch thick, and adjustable jet. to the carburetor. Electric fuel pump may be allowed; must be on separate toggle switch. Must use stock valve covers with NO spacers.
3. **Driveline:** Maximum tire size is 26 X 12 X 1/ Bar/AG tires are allowed. NO professional pulling tires are allowed (such as Cepek, Pit Bulls, ETC.). Cutting/shaving of tread us permitted. Due to tire size, alterations to final driveline, IE... upgrades to belt-tensioners, clutch springs, pulley size and gear change, are permitted. Must have reverse. May use any gear selection.
4. **Miscellaneous:** Maximum weight or tractor and driver is determined by class. Any tractors that pull in sport MAY pull in stock altered or pro-stock classes.

### **Super Pro**

1. Tractor frame can be modified.
2. Engine does not need to be original equipment, but must meet the following rules
  - a. 1 or 2 cylinders (50.5 cubic inch) > 4 cycle
  - b. Original rated at 20 horsepower or less
3. 1/16 -inch metal shield must be provided over all belts, chains, etc.
4. 1/16 -inch metal shield must be provided over turbocharger.
5. NQS pro-stock and super stock 50.5 cubic inch maximum are legal to run in this class.
6. 1/8-inch steel or 3/16-inch aluminum shields must be provided 360 degrees around the flywheel (steel flywheel only) and clutch. 4500 RPM maximum limit for cast flywheel.
7. Tractor must be stock in appearance and must have a hood, grill, seat, and fenders in place.

8. Transmission and rear axle housing need not be original equipment for the tractor but must have been original manufactured for garden tractor use. Internal parts may be modified.
9. Maximum length of 8 feet from the center of rear axle forward, including weights.  
Maximum wheelbase length 56 inches.
10. Oxidizers (i.e., nitrous oxide), pressurized fuel tanks are not allowed. There are no other limitations on fuel or fuel systems.
11. Maximum tire size 26 X 12 X12. Tire tread pattern may be bar or turf type (**NO** paddle tires). Professional pulling tires are allowed.

### **Stock Altered**

1. Must run factory looking hood and grill and must have stock length frame.
2. Engines must be Kohler, Wisconsin, Tecumseh, Briggs, Onan, Kawasaki, or Honda.
3. Single cylinder, four cycle, flathead engines only (16 horsepower maximum). NQS stock altered, and 30 cubic inch super stock allowed running in this class per NQS rules. 30 cubes **MUST** run 50 pounds. Light and **NO NITROUS**.
4. Carburetor must be Kohler type and chokes may be removed.
5. Billet heads are permitted along with after-market stock heads.
6. Porting and polishing are permitted.
7. Engine block must be OEM stock appearance. Recast blocks are allowed.
8. Tractors with 01-W engine, twin cylinder engine or engines without steel flywheels or shielding will be allowed to compete but will be limited to 4500 RPMS regardless of flywheel or shielding (20 horsepower maximum).
9. Maximum engine bore 3.38 inches, maximum crankshaft stroke 3.25 inches, 36.5 cubic inch limit.
10. Blocks may be relieved.
11. Velocity stacks allowed.
12. Carburetor must be mounted to the engine with no more than 1-inch spacer.
13. Carburetor cannot exceed 1-inch venturi (must be stock location).
14. Camshaft may be reground.
15. All engines must have a scatter shield opposite the camshaft of the engine, must be made of 1/8-inch steel or 3/16-inch aluminum, must cover full height and width of block, be attached in secure manner to frame and head or head plate.
16. **NO** oversized valves, stock size only, 1.380 inches.
17. Wheelbase 52 inches maximum.
18. Steel flywheels are mandatory, if running ultimate RPM 's.
19. All other engines cannot exceed Kohler specifications.
20. Starter pulleys must be billet aluminum or steel. Factory starter pulleys and stamped steel are not allowed.
21. Maximum valve lifts .330.
22. No welding allowed in engine blocks. NO external modifications allowed on engine blocks.
23. Maximum tire size 26 X 12 X 12. Tire tread pattern may be bar or turf type (NO paddle type). Professional pulling tires are allowed.
24. **NO** pressurized fuel tanks or nitrous oxide.
25. All thread through finned area acceptable.
26. Pumped gas or alcohol must be clear.



27. Gas specified gravity .750 maximum (tested with dielectric tester).
28. NO portion of any tractor may exceed 7-foot from the center of the rear wheels, including weight.
29. Tractor must have garden tractor rear end. Locked rear end permitted.
30. Foot peg, platform and seat must be in stock location

#### **14 & 16 Horsepower Max Stock**

1. 4000 RPM govern class must be a stock block Kohler, Briggs, or Tecumseh single cylinder, flat engines with 9 bolt heads.
2. Foot and hand throttle are permitted.
3. Fuel may be gas or race fuel **NO** alcohol or nitrous oxide, or other pressurized fuel tanks.
4. Engine must look stock from the outside.
5. Must have stock stroke for engine, all other internal modifications are acceptable.
6. Aftermarket points in ignition are permitted.
7. Head bolts must match stock OEM gaskets. Head straps are allowed.
8. OEM cast flywheels with **NO** cutting, welding, or adding weigh. Steel flywheels are acceptable.
9. Carburetor must be stock for engine or a Kohler or Walbro, carburetor spaces, velocity stacks and bottom adjusts are acceptable.
10. NO high-performance fuel pumps.
11. Maximum tires size is 26 X 12 X.12 or under Cutting is permitted. Professional pulling tires are allowed.
12. **NO** weights behind rear tires.
13. 13-inch hitch height with 1-inch hole.
14. Must use a stock garden tractor frame with axle in original location.
15. Maximum of 52-inch wheelbase.

**Farm Tractor Pulls**  
**Thursday, Friday, and Saturday**

**\*\* Any tractor that pulls Tuesday, Thursday or Friday will not be permitted to pull on Saturday**

**Each Farm Tractor class will have these divisions:**

**3.5 mph Non-Cut Tires**

- a. New or road worn tires only. NO EVIDENCE OF ALTERED TIRES! Tire size restriction in chart.
- b. Non-Turbo unless factory equip
- c. Drawbar 18" high, 24" back
- d. All weights will run **3.5** mph pace.

**Cut 3.5mph**

- a. Any style of cut on tire is permitted Tire size restriction in chart.
- b. Drawbar 20" high, 18" back
- c. All weights will run a 3.5 mph pace

**6mph Cut Tires** Any style of cut on tire is permitted

- a. Any style of cut on tire is permitted Tire size restriction in chart.
- b. Drawbar 20" high, 18" back
- c. All weights will run a 6-mph pace.

**Open Cut Tires**

- a. Any style of cut on tire is permitted Tire size restriction in chart.
- b. Drawbar 20" high, 18" back
- c. No speed limits

**RULES:**

1. General rules apply.
2. Pace classes will be paced via Agritronix system on the sled. Pull will be disqualified if speed horn blows at all after the cone set by track officials.
3. No weights may extend more than 6" beyond rear tires except orchard or utility style tractors; front weights may not extend more than 11 feet forward from center of rear axle.
4. No chains or dual wheels permitted. Four-wheel drive tractors must have front wheels disengaged.
5. When smaller diameter tire is used you may use one width larger size (one time only).
6. Drawbar must be equipped with a clevis or hitching device not more than 1 "thick and not less than ½ "thick. Hitch device must be unobstructed by weights. Top of hitch adjuster must not be attached above center line of axle or hub.
7. Engine must be agriculture or industrial type engine.
8. Exhaust pipe must extend above steering wheel except for stock rear/side exhaust system.
9. A tractor may register for only three (3) classes. Tractors may pull multiple classes at the same weight if their tractor meets the class requirements.
10. Rules/classes subject to change, if necessary, by the committee.

**Thursday, August 11<sup>th</sup>, 2022, – Registration & Weigh in 5:30 Pm, Start 6:30 PM**

<b>Dept. 22</b>	<b>Farm Tractor Pulls</b>	
<b>Section 1</b>	<b>Entry FEES \$20.00</b>	
<b>Premiums</b>	<b>1st-\$30.00 2nd-\$25.00 3rd-\$20.00 4th-\$15.00 5th-\$10.00</b>	
<b>Class</b>	<b>Weight</b>	<b>Tire Sizes</b>
22120	<b>3,500</b> Cut 4 MPH	15.5x38 or 16.9x34
22121	<b>3,750</b> Cut 4 MPH	15.5x38 or 16.9x34
22122	<b>4,000</b> Cut 4 MPH	15.5x38 or 16.9x34
22123	<b>4,500</b> Cut 4 MPH	15.5x38 or 16.9x34
22124	<b>5,500</b> Cut 4 MPH	15.5x38 or 16.9x34
22125	<b>6,500</b> Cut 4 MPH	15.5x38 or 16.9x34
22126	<b>7,500</b> Cut 4 MPH	15.5x38 or 16.9x34

**Friday, August 12<sup>th</sup>, 2022, – Registration & Weigh in 5:30 Pm, Start 6:30 PM**

<b>Dept. 22</b>	<b>Farm Tractor Pulls</b>	
<b>Section 1</b>	<b>Entry FEES \$20.00</b>	
<b>Premiums</b>	<b>1st-\$30.00 2nd-\$25.00 3rd-\$20.00 4th-\$15.00 5th-\$10.00</b>	
<b>Class</b>	<b>Weight</b>	<b>Tire Sizes</b>
22142	<b>3,500</b> Any Cut 6 MPH	18.4x38
22143	<b>3,500</b> Open	18.4x38
22144	<b>3,750</b> Any Cut 6 MPH	18.4x38
22145	<b>3,750</b> Open	18.4x38
22146	<b>4,000</b> Any Cut 6 MPH	18.4x38
22147	<b>4,000</b> Open	18.4x38
22148	<b>4,500</b> Any Cut 6 MPH	18.4x38
22149	<b>4,500</b> Open	18.4x38
22150	<b>5,500</b> Any Cut 6 MPH	18.4x38
22151	<b>5,500</b> Open	18.4x38
22152	<b>6,500</b> Any Cut 6 MPH	18.4x38
22153	<b>6,500</b> Open	18.4x38
22154	<b>7,500</b> Any Cut 6 MPH	18.4x38
22155	<b>7,500</b> Open	18.4x38

Saturday August 13<sup>th</sup>, 2022, - Registration and Weigh in 2:00 PM, Start at 3:00 PM

**\*\* Any tractor that pulls Tuesday, Thursday or Friday will not be permitted to pull on Saturday**

<b>Dept. 22</b>	<b>Stock Farm Tractors</b>	
<b>Section 1</b>	<b>Entry Fee \$20.00</b>	
<b>Premiums</b>	<b>1st-\$30.00 2nd-\$25.00 3rd-\$20.00 4th-\$15.00 5th-\$10.00</b>	
<b>Class</b>	<b>Weight</b>	<b>Tire Size</b>
22160	<b>3,500</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22161	<b>4,000</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22162	<b>4,500</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22163	<b>4,500</b> 8 MPH Non-Cut Tire	15.5x38 or 16.9x34
22164	<b>5,000</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22165	<b>5,500</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22166	<b>5,500</b> 8 MPH Non-Cut Tire	15.5x38 or 16.9x34
22167	<b>6,000</b> 3.5 MPH Non-Cut Tire	15.5x38 or 16.9x34
22168	<b>7,000</b> 3.5 MPH Non-Cut Tire	18.4x38
22169	<b>7,000</b> 8 MPH Non-Cut Tire	18.4x38
22170	<b>8,000</b> 3.5 MPH Non-Cut Tire	18.4x38
22171	<b>9,000</b> 3.5 MPH Non-Cut Tire	18.4x38
22172	<b>9,000</b> 8 MPH Non-Cut Tire	18.4x38
22173	<b>10,000</b> 3.5 MPH Non-Cut Tire	18.4x38
22174	<b>11,000</b> 8 MPH Non-Cut Tire	18.4x38
22175	<b>12,000</b> 8 MPH Non-Cut Tire	18.4x38
22716	<b>13,000</b> 8 MPH Non-Cut Tire	18.4x38